

//

## 1. Tandon



Tersedia bahan baku Polyethylene, fiberglass, dan stainless Steel

Tahan terhadap benturan

Tersedia dalam berbagai ukuran

Merk : Penguin

"Type : TB 32

Capacity : 300 liter

d tutup : 265 mm"

"Type : TB 53

Capacity : 520 liter

d Tutup : 265 mm"

"Type : TB 110

Capacity : 1050 liter

d Tutup : 400 mm"

"Type : TB 500

Capacity : 5100 liter

d Tutup : 600 mm"

## 2. Ball VLV HDPE PLC dari PVC ke drat dalam



Diameter : 1"

Fungsi : berguna untuk membuka dan menutup aliran air

Material : Polyethylene

## 3. Disc Filter Pump



Fungsi : Untuk menyaring air. Di dalamnya berupa piringan.

Material : Polyethylene

Pressure : 6 barr

Micron : 125

Mesh : 120

Max Flow : 5 m<sup>3</sup>/hr"

#### 4. Selang PE



Material : Polyethylene

Diameter : 5 mm

Material : Polyethylene

Diameter : 16 mm

1 roll : 400 m

#### 5. Director



Diameter : 16mm x 1"

Fungsi : menghubungkan antara sumber air dengan pipa PPC

Material : Polyethylene

#### 6. Tape Lock



Fungsi : sebagai konektor ke drip tipe

Material : Polyethylene

### 7. TEE



Diameter : 16mm

Fungsi : pipa yang berbentuk T untuk pembagi aliran

Material : Polyethylene

Brand : Antelco (Australia)

ada drat nya

### 8. Joiner



Diameter : 16mm

Fungsi : sebagai konektor antar dua pipa yang ukurannya sama

Material : Polyethylene

### 9. Elbow



Diameter : 16mm

Fungsi : sebagai konektor antar pipa yang alirannya berbentuk siku

Material : Polyethylene

### 10. Regulating Stik & Adaptor



Material : Polyethylene  
Spesifikasi : 0,8 bar  
Kapasitas : 2 liter/jam

### 11. Drip Pipe (per meter)



Material : Polyethylene  
Jarak antar lubang 50 cm  
D : 16 mm  
1 roll : 1100 m

### 12. Take Off



Kode : 28TO1212EPL  
Diameter : 16 mm  
Fungsi : sebagai konektor ke drip tipe biasa dikombinasikan dengan Grommet  
Material : Polyethylene"

### 13. Grommet



Alat untuk menutup aliran  
Biasanya dikombinasikan dengan take off  
Bahan : Polyethylene  
D : 2,9 cm  
Brand : Philmac

### 14. End Line



Aplikasi untuk menutup saluran pada selang PE 16 mm  
Material : Polyethylene"

### 15. Punch



Alat untuk melubangi selang  
Material : Polyethylene  
Merk : Philmac

### 16. Automatic Controller



- > Number of stations: 4 station
- > Type: Fixed
- > Enclosure: Indoor
- > Independent programs: 2 (customisable)
- > Start times per program: 4 (customisable)
- > Max station run time: 4 hrs
- > Compatible with Hunter Clik sensors and other micro-switch type weather sensors
- > Rain sensor bypass
- > Programmable rain delay: 1 to 7 days
- > Manual cycle
- > Test program allows for quick system checks
- > Quick Check™
- > Non-volatile memory
- > Automatic short circuit protection

- > Seasonal adjustment (global): 10% to 150%
- > Delay between stations (maximum): 4 hrs
- > Customisable programs enable the controller to be simplified

### 17. Sprinkler Gyronet



Koneksi : ½". Kapasitas : 250 L/h  
Diameter pancaran : 8 m. pressure : 3 bar  
Sudah termasuk konektor ke pipa paralon ½"

### 18. Meganet



Produk by Netafim  
½"

High water trajectory angle - for vegetables and open field crops , open field nurseries, crops germination, frost fighting, cooling fruit orchards and roof dust cleaning.  
Low water trajectory angle - for under tree irrigation and shade/net houses  
Diameter : 17 m"


### 19. Octa emitter



Pressure : 0,5 - 2 barr  
Kapasitas : 10 - 11 liter/jam  
made in irritec

### 20. Rotator R2000 WF

  
081297780762  
Majestic: 33075600 liter/detik

  
081297780762  
Majestic: 1005-21,5 liter/jam

  
081297780762  
Majestic: 150 liter/jam

  
081297780762  
Majestic: 4000-6100 liter/detik